WO 2005/045252 PCT/EP2004/012577

CLAIMS

- Multistage centrifugal compressor comprising 1. least one stage 10 which, in turn, comprises a lower half-tank 11, an upper half-tank 12, a series of lower half-diaphragms 16, a shaft 13 equipped with a series of 5 rotors 14, a series of upper half-diaphragms 18, a lower an upper suction halfsuction half-diaphragm 51, diaphragm 52, characterized in that the lower suction half-diaphragm 51 and the upper suction half-diaphragm 52 include a portion 71 and a portion 72, respectively, 10 suitable for being coupled with the lower half-diaphragms 16 and with the upper half-diaphragms 18, respectively, to form a first pile 41 of lower half-diaphragms 16 and a second pile 42 of upper half-diaphragms 18, respectively. The multistage centrifugal compressor according to 15 claim 1, characterized in that said shaped cylindrical section 71 comprises a series of annular housings 59 suitable for being coupled with lower half-diaphragms 16 and in that said shaped cylindrical section 72 comprises
 - 3. The multistage centrifugal compressor according to claim 1, characterized in that each lower half-diaphragm 16 includes a section 81 suitable for being respectively

a series of annular housings 60 for balancing the axial

stress received during the functioning of the multistage

20

25

centrifugal compressor.

WO 2005/045252 PCT/EP2004/012577

coupled with an internal housing 59 of the relative lower suction half-diaphragm 51, and in that each upper half-diaphragm 18 includes a section 82 suitable for being respectively coupled with an internal housing 60 of the relative upper suction half-diaphragm 52.

- 4. The multistage centrifugal compressor according to claim 1, characterized in that the lower suction half-diaphragm 51 comprises a series of radial shaped grooves 61 and, correspondingly, the upper suction half-diaphragm 52 comprises a series of radial shaped grooves 62.
- 5. The multistage centrifugal compressor according to claim 1, characterized in that the lower suction half-diaphragm 51 includes a section with a shaped basis 63, open at the centre and, correspondingly, the upper suction half-diaphragm 52 includes a section with a shaped basis 64, open at the centre.

10

20

6. The multistage centrifugal compressor according to claim 1, characterized in that the lower suction half-diaphragm 51 and the upper suction half-diaphragm 52 respectively include supporting feet to adapt the multistage centrifugal compressor to the configuration with a horizontal opening of the tank.